

REFLEX S PAD



Make a difference with REFLEX:

Outstanding Performance & Versatility:
Deep Cleaning. Multifunctional and Ergonomical.



Climate & Eco-friendly:
Less water and chemicals. Residue Free Cleaning.



Improves cleaning economy:
Saves time and space and cuts total costs.



Product code: **Colour code:** **Dimensions:**

10-0350-2	blue	15 x 18 cm	REFLEX S PAD, AbrasiveSoft, Multiple use, 32 grs/pcs
-----------	------	------------	--

10-0354-2	red	15 x 18 cm	REFLEX S PAD, AbrasiveSoft, Multiple use, 32 grs/pcs
-----------	-----	------------	--

Package: 5 pcs in pp bag, 40 pcs x 5-pack per transport box

Application areas:

REFLEX S PAD is designed for hard top, ceramic and chrome surfaces for hygienic cleaning results: e.g. toilets and sinks at healthcare facilities, nurseries, schools, offices, and public, hospitality and residential buildings. S PADS can also replace abrasive sponges on surfaces e.g. at sport facilities, food industry, and locker rooms.



Healthcare sector



Public Areas & General Buildings



Food Industry & HoReCa

How to use the system:

REFLEX S PAD is double-sided with woven block pattern combining PET film and Ultra Microfibre structure removing grease, lime and other stubborn dirt from the surface. Before use, test that the surface is suitable for cleaning with microfibre. Polycarbonate surfaces should not be cleaned with microfibre.

CHARGING:

REFLEX S PADS can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

CHARGING S PADS ON THE TROLLEY:

1. Put S PADS in a container, e.g. 6 Ltr. rectangle bucket or box with lid.
2. Pour the desired fluid equally over the pads inside the container.
3. Leave for a while with closed lid. Ready to clean!

SPRAY METHOD:

Spray directly to the surface to be cleaned and wipe the sprayed area with S PAD. Alternatively, spray on the pad and start wiping.

ABOUT DOSING:

Avoid overdosing regardless of the charging liquid. Some chemicals may cause damage to user, material and/or environment. Depending on surface circumstances, charge with 5-50 ml of liquid per S PAD.






Rekola supports Residue Free Cleaning.

Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health.

REFLEX S PADS are designed to reduce and remove residue that resist traditional cleaning methods.

For more information please contact Rekola.

REKOLA

Maintenance	
Laundry: 	Rinse twice with cold water to ensure all cleaning chemicals are removed. Main program for synthetic fibers at 60°C or less is preferred. Rinse twice at 40°C to ensure all laundry agents are removed. Adjust temperatures and water volumes accordingly. Machine drum can be filled with S PADS up to 60% load. In case of drying, use tumble drying at 40°C. Do not use bleach or softener. Low water level during processing or overloading the washing machine (max 50% of door window) may cause irreversible damage to pads.
Disinfection:	Non-bleach disinfectant* laundry agent and autoclaving may be used if required. *e.g. peroxide based; this may affect colours
Durability: 	500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough abrasive surfaces and intensive rubbing of open structures like drains may reduce the pads' lifetime expectations.
Components	
Body:	50% split Ultra Microfibre / 50 % PET film; 90% PES , 10% PA . UMF F= 0,154 Dtex. Inside 2 layers of 100% UMF ; 80% PES , 20% PA .
Borders:	Overlock and piping 100% PES .
Characteristics	
Shrinkage:	SGS tested < 6% according to recommended washing instructions. Shrinking may cause slight deformation, which does not affect the functionality.
Colour fastness:	4-5 <i>standard request ≥ 3-4</i>
Abrasion:	It is not advised to predispose softer material surfaces to the abrasion generated during use.
Weber & Leucht S301/1.3 dirt removal:	Ceramic tile SF 11 Dust A23 Damp 93% <i>standard request ≥ 70</i>
	PVC surface PL-03 Dust A23 Damp 87% <i>standard request ≥ 70</i>
	Ceramic tile SF 11 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i>
	PVC surface PL-03 Muddy dirt A05 Damp 100% <i>standard request ≥ 70</i>
Bacteria reduction:	E-coli 99,89% log >2,96 S. aureus 99,31% log 2,16 
Disposing:	REFLEX S PADS are made of purely synthetic materials: they may be used in recycling programs, or because of their high energy value and zero emissions other than CO ₂ and water, can be safely disposed by controlled energy-supply programs.
Guarantee	
500 uses and washes according to producer's guidelines at 60°C, under general hygiene cleaning circumstances at a maintained surface. Extended usage can be achieved if optimal laundry and cleaning conditions are considered. For instructions and details, contact your local distributor.	